

REFER TO LAYOUT DRAWINGS FOR ADDITIONAL DIMENSIONAL INFORMATION

REFER TO SCHEDULE FOR PARTITION TYPES, SEE CORRESPONDING TAGS FOR ENLARGED ROOM PLANS, SECTIONS AND DETAILS.

PROVIDE 4" CRITICAL DIMENSIONS BETWEEN DOOR OPENING AND WALL AT HINGE SIDE, U.N.O.

PROVIDE 18" CRITICAL DIMENSIONS BETWEEN DOOR OPENING AND ALL OBSTRUCTIONS AT PULL SIDE OF DOOR.

PROVIDE 12" CRITICAL DIMENSION BETWEEN DOOR OPENING AND ALL OBSTRUCTIONS AT HINGE SIDE OF DOOR.

WALLS BETWEEN ADJACENT ROOMS - ELECTRICAL OUTLET LOCATION, INCLUDING 120V AND TELEPHONE OUTLETS, SHALL BE OFFSET 6" MIN. HORIZONTALLY - BACK TO BACK OUTLETS ARE NOT ALLOWED

COMMUNICATION FEATURE ROOM MUST HAVE A VISIBLE NOTIFICATION DEVICE FOR THE TELEPHONE.

ACCESSIBLE ROOMS SHALL BE EQUIPPED WITH TOGGLE - TYPE SWITCHES

PROVIDE ADEQUATE F.R.T. BLOCKING AT ALL PARTITIONS TO HAVE WALL MOUNTED CASEWORK, MILLWORK, OR SHELVING TO SUPPORT A MAXIMUM LOADING. DETERMINE LOCATION OF BLOCKING FOR ARCHITECTURAL AND MEP EQUIPMENT AS REQUIRED.

6. COORDINATE SWITCH, STROBE, THERMOSTAT, AND FIRE EXTINGUISHER LOCATIONS SO AS TO AVOID FURNITURE PANELS, ACCESS WALL PANELS, SCREENS CASEWORK AND WALL CABINETS.

1. REFER TO SCHEDULE FOR DOOR TYPES AND HARDWARE.


| PLAN | ELEV. | |
|---|---|---|
|  |  | DUPLEX OUTLET |
|  |  | QUADPLEX OUTLET |
|  |  | GFI OUTLET |
|  |  | TELEPHONE OUTLET |
|  |  | TV OUTLET |
|  |  | SWITCH |
|  |  | REMOTE THERMOSTAT |
|  |  | SMOKE DETECTOR |
|  |  | STROBE (IN C.F. ROOMS ONLY) |
|  |  | FIRE HORN/STROBE (IN C.F. ROOMS ONLY, OMIT FIRE HORNS WHEN THESE ARE USED) |
|  |  | FIRE HORN (NON-C.F. ROOMS) |
|  |  | SIDEWALL SPRINKLER HEAD |
|  |  | DOORBELL LIGHT (C.F. ROOMS ONLY) |
|  |  | HSIA (WIRED WHERE APPLICABLE) |
|  |  | JUNCTION BOX |
|  |  | EXHAUST FAN |
|  |  | LIGHT AT CEILING |
|  |  | DOORBELL - MOUNT AT 46" AFF TO CENTER OF BUTTON (C.F. ROOMS ONLY) |

- 1 HARDWIRED PACKAGED TERMINAL AIR CONDITIONER (PTAC) UNIT.
- 2 EXTERIOR WINDOW AND ASSOCIATED TREATMENTS
- 3 BARN DOOR ON EXPOSED HARDWARE - REFER TO DOOR SCHEDULE FOR MIRROR INSET APPLICATION
- 4 COMMUNICATING DOOR LOCATION WHEN USED
- 5 ARCHITECTURAL MILL WORK VALANCE PAINT TO MATCH GENERAL WALL COLOR - ANCHOR FROM CEILING
- 6 LIGHTS IN THIS AREA MUST BE DAMP LOCATION RATED W/ SHATTER PROOF LENSES.
- 7 WALL MOUNTED VANITY LIGHT - PROVIDE JUNCTION BOX, COORDINATED WITH FIXTURE
- 8 STARTING POINT OF TILE - BEGIN WITH FULL TILE
- 9 ALL ROOMS TO HAVE HSIA PER HILTON STANDARDS. IF HARDWIRED INTERNET ACCESS IS DESIRED, A RECEPTACLE MUST BE PLACED @ 34" A.F.F.
- 10 SHOWER / BATH DRAIN LOCATION
- 11 NO FINISHES UNDER SHOWER PAN / TUB
- 12 PROVIDE DEDICATED ELECTRICAL CIRCUIT FOR EACH UNDERCOUNTER APPLIANCE
- 13 DOORBELL ON/OFF SWITCH FOR COMMUNICATION FEATURE ROOM ONLY - SIGNAGE AS REQUIRED
- 14 THRESHOLD - REFER TO STANDARDS MANUAL
- 15 SHOWER INDICATED: BATH TUBS MAY BE SUBSTITUTED - REFER TO STANDARDS
- 16 DASHED BOXES AND CIRCLES REPRESENT ACCESSIBLE CLEAR FLOOR AREAS - REFER TO ACCESSIBLE PLANS SHEET FOR ADDITIONAL INFORMATION
- 17 ACCESSIBLE DRAPERY CONTROL
- 18 DESK MUST PROVIDE MIN. 30" WIDE CLEAR FLOOR SPACE AND A MIN. 27" HIGH KNEE CLEARANCE
- 19 PROVIDE DRAIN IN THIS LOCATION IN GUEST BATHS EQUIPPED WITH ROLL-IN SHOWERS. DISH DRAIN AT A 6" RADIUS (1.48 SLOPE MAX) PROVIDE TRAP PRIMER
- 20 FLAT SCREEN TV
- 21 CLOCK
- 22 TELEPHONE
- 23 CENTER SCONCE ABOVE NIGHTSTAND
- 24 EDGE OF PTAC SKIRT AT FLOOR

GF-100 ACTIVITY CHAIR
GF-101 OTTOMAN
GF-102 SOFA SLEEPER
GF-103 SINGLE ARM SOFA SLEEPER
GF-104 SINGLE ARM CHAISE
GF-105 LOUNGE CHAIR
GF-201 GUESTROOM VANITY LIGHT
GF-202 REDUCED TABLE LAMP AT NIGHTSTAND
GF-203 SINGLE NIGHTSTAND SCONCE
GF-204 DOUBLE NIGHTSTAND SCONCE
GF-205 DESK LAMP
GF-206 FLOOR LAMP
GF-300 STREAMLINE UNIT
GF-301 KING HEADBOARD
GF-302 QUEEN HEADBOARD
GF-303 DOUBLE HEADBOARD
GF-304 NIGHTSTAND
GF-305 NIGHTSTAND WITH POWER
GF-306 CLOSET NIGHTSTAND WITH POWER
GF-307 C-TABLE
GF-308 68" VANIT AT GUEST BATH
GF-309 68" VANIT AT GUEST BATH
GF-310 ADA VANITY AT GUEST BATH
GF-311 STREAMLINE DIVIDER UNIT
GF-312 ADA STREAMLINE UNIT
GF-313 ADA STREAMLINE DIVIDER UNIT
GF-314 62" VANITY AT GUEST BATH
GF-315 STREAMLINE DESK UNIT
GF-400 WINDOW TREATMENT WITH FTAC
GF-401 WINDOW TREATMENT WITHOUT FTAC
GF-402 ROLLER SHADE
GF-501 ARTWORK AT GUESTROOM
GF-502 ARTWORK AT GUEST BATH
GF-503 ARTWORK AT SOFA IN SUITES
GF-504 FRAMED MIRROR AT VANITY
GF-505 FRAMED MIRROR AT AD VANITY
GF-600 KING BED BASE
GF-601 KING MATTRESS SET
GF-602 KING BEDDING SET
GF-603 ADA KING BED BASE
GF-604 QUEEN BED BASE
GF-605 QUEEN MATTRESS SET
GF-606 QUEEN BEDDING SET
GF-607 ADA QUEEN BED BASE

| | | |
|-----|----------------|------------------------------|
| B | BASE | NOTE: |
| C | CARPET | REFER TO FF&E SPECIFICATIONS |
| MIR | MIRROR | MANUAL AND COLOR AND |
| PT | PAINT | MATERIALS SPECIFICATIONS |
| ST | STONE | MANUAL FOR FURNITURE ITEMS |
| SF | SPECIAL FINISH | NOT IDENTIFIED WITHIN THESE |
| T | TILE | DRAWINGS |

| | |
|---|---|
|  | RECESSED LIGHT SCONCE |
|  | RECESSED ADJUSTABLE DOWN LIGHT FIXTURE |
|  | RECESSED FLUORESCENT LIGHT FIXTURE 24" x 48" |
|  | RECESSED FLUORESCENT LIGHT FIXTURE 24" x 24" |
|  | SURFACE MTD. DOWN LIGHT FIXTURE 24" x 48" |
|  | WALL MOUNTED LIGHT SCONCE |
|  | PENDANT LIGHT FIXTURE |
|  | DECORATIVE PENDANT LIGHT FIXTURE |
|  | DIRECTIONAL EMERGENCY EXIT LIGHT |
|  | BATH EXHAUST FAN |
|  | RECESSED SHOWER DOWNLIGHT |
|  | LINEAR DIFFUSER |
|  | RETURN AIR GRILLE |
|  | DIFFUSER |
|  | WALL MOUNTED SPRINKLER |
|  | CEILING SPRINKLER |



ISSUE

Issued for Permit
08.05.2016

PROJECT: 16-018

Hampton Inn & Suites

New Stanton, PA 15672

OWNER

Stanton Hospitality LLC

52 Blueberry Lane,
Grove City, PA 16127

THESE DRAWINGS ARE FOR REVIEW OF DESIGN AND SCOPE DESCRIPTION ONLY. NO REPRESENTATION IS MADE TO THE ACCURACY OF THE DRAWINGS WITH RESPECT TO EXISTING DIMENSIONS OR CONDITIONS. ALL CONSULTANTS AND CONTRACTORS MUST VERIFY ANY AND ALL DIMENSIONS AND CONDITIONS WHICH ARE CRITICAL TO THEIR WORK. THESE DRAWINGS ARE INSTRUMENTS OF SERVICE AND ARE THE INTELLECTUAL PROPERTY OF JMAC ARCHITECTS. ANY UNAUTHORIZED USE OR REPRODUCTION IS PROHIBITED.

[illegible]

| No. | Issue Date | Project Statu |
|-----|------------|---------------|
|-----|------------|---------------|

Enlarged Guestroom
Elevations - Accessible
King Studio

As indicated

A-525A